

Magma MX295

Top grade sheep hide cut level D welder's gauntlet



SPECIFICATION & CHARACTERISTICS

Code MX295

Size Range 8-11

Packaging 10 pairs/pack - 6 packs/case

Materials Top grade sheep grain leather with spectra lining

Characteristics

- ✓ Top grade sheep grain leather.
- ✓ Superbly soft and supple leather.
- ✓ Pigment free to retain flexibility.
- ✓ Wide fit for ease of donning.
- ✓ Increased length for extra protection.
- ✓ Thumb and crotch reinforcement.
- ✓ Heat resistant Kevlar stitching.
- ✓ Cut resistant lining around the palm of the glove to protect the wearers from cut risks.

STANDARDS COMPLIANCE

EN388: 2016

Mechanical Hazards

Protection against mechanical hazards in respect of physical and mechanical stress caused by abrasion, blade cut, tear and puncture. The table below indicates the glove's resistance to:

2 = Abrasion	(Performance Index 1-4)
X = Blade Cut* (Coup)	(Performance Index 1-5)
4 = Tear	(Performance Index 1-4)
3 = Puncture	(Performance Index 1-4)
D = Cut (EN ISO 13997)	(Rating A-F)

NOTES:

Where 1 indicates the lowest performance. X that the test was not performed or not possible. A 0 rating indicates that during the test level 1 was not reached.

*Gloves should not be used when working with serrated blades.

EN407

Hot Thermal Hazards

This standard specifies thermal performance for protective gloves against heat and/or fire. The table below indicates the glove's resistance to:

4 = Flammability	(Performance Index 1-4)
1 = Contact heat	(Performance Index 1-4)
3 = Convective heat	(Performance Index 1-4)
X = Radiant heat	(Performance Index 1-4)
4 = Small splashes of molten metal	(Performance Index 1-4)
X = Large splashes of molten metal	(Performance Index 1-4)

NOTES:

Where 1 indicates the lowest performance. X that the test was not performed or not possible. A 0 rating indicates that during the test level 1 was not reached.

EN12477

Manual Metal Welding Hazards

Rating: Type A



2X43D



413X4X